

Over 5000 VXI cards and mainframes in stock. 1000's of pieces of Test Equipment in stock.



Looking for Test Equipment?
Visit us on the web at
www.recycledequipment.com

Recycled Equipment buys, sells, and repairs VXI cards, VXI mainframes and Test Equipment. We have tens of thousands of pieces of Electronic Test Equipment and one of the worlds largest selections of VXI cards. We have VXI cards by almost every manufacture; from Agilent to Ziatech. **Every item on our website is IN STOCK and ready to ship with in 24 hours.**

Sell your equipment for cash

Recycled Equipment is interested in buying your surplus equipment! Call us today at **(410)685-1997** or email to **recycled@usimperio.com**

Sell your equipment on consignment

Recycled Equipment can sell your equipment on consignment. This allows you to get retail prices for your equipment with out the hassle.

(410)685-1997 sales@recycledequipment www.recycledequipment.com



Tenney's Benchmaster temperature humidity test chambers are capable of simulating a wide range of temperature or temperature and humidity conditions. The five cubic foot work space will readily accept equipment as large as a 19" relay rack. These chambers are well-suited for use in electronic, military, and pharmaceutical quality assurance and reliability testing, as well as research testing and production processes. In keeping with the needs of today's lab, we specifically designed these temperature humidity chambers to have a compact exterior, yet an ample interior workspace to maximize valuable floor space.



Temperature Humidity Test Chamber and Humidity Room Features

- Vapor-tight interior liners made of 100% continuously welded stainless steel
- Control system for humidified units provides fully automatic, PID, chamber control through a user-friendly alpha-numeric display
- Temperature Humidity Test Chambers with humidity are constructed of 100% non-corroding parts and have a low-water protection system
- Uniform conditions are assured through the use of a vertical-down recirculating conditioning stream

Standard Features at a Glance:

- Vapor tight interior made of 100% stainless steel
- Non-settling, asbestos-free insulation
- Proprietary VersaTenn III control system on BTRC
- Watlow F4 controller on BTC
- Control tolerance of $\pm 0.3^{\circ}\text{C}$
- Hermetic refrigeration system
- Tenney VaporFlo humidity system
- Low mass nichrome, open wire heating system
- NEC wiring compliance
- Vertical-down recirculating conditioning system
- Double silicon gaskets on doors
- 2" diameter access port with plug
- $\pm 2\%$ RH typical after stabilization

Options:

- IEEE/488 interface
- LinkTenn software for Windows that permits your computer to control up to 10 chambers
- RS422, 423, 232, or 485 interface assemblies
- Water demineralizer
- Water reservoir for humidity system (5 gallon)
- Recirculating system for humidity water
- Viewing window, 6" x 8", thermally insulated and heated
- Interior lighting
- Shelving, adjustable and removable
- Automatic CO2 or LN2 cooling boost system
- Automating boost heating system
- GN2 purge system
- Recording instruments
- Redundant thermal protection and alarm system
- External dryer for obtaining humidity as low as 5% (to 20°C)
- Alternate power supply wiring
- Chamber cart with casters

In line with our policy of continual product improvement, Tenney Environmental reserves the right to incorporate and use material to conform to the latest design of our products in keeping with the specifications of this equipment. Please discuss specific test and cycling requirements with our sales department.

Gruenberg, Blue M, Tenney, Lunaire

Mailing Address: P.O. Box 150 | White Deer, PA 17887-0150 | USA |

Phone : (570) 538-7200 | Fax: (570) 538-7380

Physical Address: 2821 Old Route 15 | New Columbia, PA 17856-9396

TPSinfo@spx.com

www.thermalproductsolutions.com



Tenney Benchmaster Chamber Specifications

Model		BTC	BTRC
Workspace	W	20/51	
	D	19.25/49	
	H	22/56	
Exterior	W	57/145	62/157
	D	34/86	
	H	34.5/88	

Overall dimensions in inches/centimeters

Temperature range

Low	$^{\circ}\text{C}$	-73
High	$^{\circ}\text{C}$	+200

Change rates in minutes

Ambient to $^{\circ}\text{C}$ Chamber Empty	200 $^{\circ}$	30
	150 $^{\circ}$	20
	93 $^{\circ}$	15
	65 $^{\circ}$	10
	0 $^{\circ}$	5
	-18 $^{\circ}$	10
	-34 $^{\circ}$	12
	-40 $^{\circ}$	15
	-54 $^{\circ}$	25
	-65 $^{\circ}$	40
	-70 $^{\circ}$	Ultimate

Live load capacity in watts (humidity system off)

Temperature $^{\circ}\text{C}$	+25 $^{\circ}$	1000	900
	+10 $^{\circ}$	900	800
	-18 $^{\circ}$	750	600
	-34 $^{\circ}$	550	450
	-40 $^{\circ}$	500	400
	-54 $^{\circ}$	400	300
	-65 $^{\circ}$	180	150

Utilities, etc.

Refrigeration		(2) 1 HP	
Heater Capacity		2 KW	
Humidifier	Watts	-	750
	GPH	-	0.3
AMPS @ 230V, 1 \emptyset		24	v24
AMPS Fuse		35	
Unit Weight	LBS	500	